

A multi-grade superior lubricating oil developed specifically for large motorcycle four-stroke gasoline engines working under severe duty conditions.

Customer benefits:

- Prevent wet clutch slippage
- Keeping engine clean and providing excellent protection against piston deposit formation
- Providing optimum protection against rust and wear
- Protect vital gear & clutch component to extend its service life.

Performance standards:

- API: SL/CF
- JASO: MA2

Typical properties:

Properties	Unit	Test Method	Typical Value		
			5W-40, API: SL, JASO: MA2	10W-30, API: SL, JASO: MA2	20W-40, API: SL, JASO: MA2
Grade	-		5W-40, API: SL, JASO: MA2	10W-30, API: SL, JASO: MA2	20W-40, API: SL, JASO: MA2
Specific Gravity @ 15°C	g/cm ³	ASTM D-1298	0.86	0.866	0.89
Kinematic Viscosity @ 40°C	mm ² /S	ASTM D-445	93	77	125
Kinematic Viscosity @ 100°C	mm ² /S	ASTM D-445	14.5	12	15.3
Viscosity Index	-	ASTM D-2270	162	151	127
Flash Point	°C	ASTM D-92	230	226	236
Pour Point	°C	ASTM D-97	-36	-36	-24
TBN	mg KOH/g	ASTM D-2896	8	8	8
CCS Viscosity	cP	ASTM D-5293	6500 (-30)	6800 (-25)	9000 (-15)