



RASCH 4T PRIME

SEMI SYNTHETIC / MINERAL

PRODUCT DESCRIPTION:

RASCH 4T PRIME is recommended for high-performance 4T motorcycles that delivers high power efficiency and acceleration. It exceeds the fuel economy and engine cleaning requirements. It also offers excellent engine protection and superior clutch operation in all driving conditions. It is excellent in maintaining high engine power and fuel economy with longer drain interval.

APPLICATION:

Recommended for all scooters and motorcycles with 4T engines. Suitable for Honda, Yamaha, Suzuki, Kawasaki, Korean and Chinese motorcycles.

FEATURES & BENEFITS:

- Excellent shear stability
- Provides high temperature protection
- Outstanding wet clutch protection for maximum power transfer and smooth shifting
- Excellent wear and corrosion protection
- Maximizes power and acceleration
- Added protection against harmful deposits

PERFORMANCE LEVELS: Meets or Exceeds:

- API Service Category SJ and JASO MA2

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	RASCH 4T PRIME	
Grade			10W-60	20W-50
Kinematic Viscosity @ 104°F /40°C	D-7042	cSt	185	185
Kinematic Viscosity @ 212°F /100°C	D-7042	cSt	25.3	20.4
Viscosity Index (min)	D-2270	-	170	129
SP. Gravity @15°C/ 60°F	D-4052	g/cm ³	0.860	0.890
Flash Point (min)	D-92	°C	230	236
Pour Point (max)	D-97	°C	-36	-24
TBN	D-2896	Mg KOH/g	7	7
CCS, (°C)	D-5293	m.Pa.S	6800 (-25)	9200 (-25)

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website Runol.net

